

## How far is the distribution box from the controlled equipment



### Overview

Depth: A minimum of 3 feet (900 mm) in front of the electrical panel for installations up to 600V. 5 feet (2 meters) or the height of. As a licensed electrician, ensuring proper nec working clearance around electrical equipment is not just a matter of compliance—it's a fundamental requirement for safety and serviceability. 26 (A)] and dedicated space to provide access to, and protection of, equipment [110. Equipment that may need examination, adjustment, servicing, or maintenance while energized. Is distance satisfactory to protect power distribution boxes (breaker boxes, disconnects ranging from anywhere from 50 volts to 440 volts) from damage in active warehouses with stacked material, fork truck traffic, and pedestrian traffic; or does there need to be a protective barrier?

If distance. These requirements vary depending on whether the electrical equipment is rated at (1) 1,000 volts or less (See, Article #2) or (2) over 1,000 volts.



## Article Content

Safe Clearances for Electrical Equipment: Working Space and ...

The dedicated equipment space is commonly referred to as the equipment footprint (the space equal to the width and depth of the equipment). The dedicated equipment space also extends from the floor to ...

Q& A: Is distance satisfactory to protect electrical disconnects?

For indoor electrical installations, the dedicated space must be of equal depth and width to that of the equipment itself and extend from the floor to a height of 1.83 meters (6 feet) above the ...

NEC Article 110.34: Electrical Room "Basics"

Minimum clearances are established for work spaces in front of high voltage - electrical equipment such as switchboards, control panels, switches, circuit breakers, switchgear and motor controllers. These ...

Minimum Clearance Around Electrical Panels (Carrying 600 Volts or ...

NEC 110.26 and 29 CFR 1910.303 (g) (1) require sufficient access and working space around electric equipment to allow ready and safe operation and maintenance of such an equipment. Both the ...

Electrical Panel Locations

Electrical equipment must have a minimum 30" wide clear working space laterally in front of the equipment. This does not have to be centered on the equipment, but the electrical panel door ...

Working Clearances, based on the 2020 NEC

For large equipment containing overcurrent, switching, or control devices, an entrance to (and egress from) the required working space at least 24 in. wide and 6½ ft high is required at each end of the ...

NEC Working Clearance Requirements: A Visual Guide (110.26)

Per NEC 110.26 (D), all working spaces must have a minimum Electrical equipment headroom of 2.0 m (6 ft 6 in), measured from the floor or platform to the ceiling or any overhead obstruction like pipes or ...

Electrical Panel & Gear Clearance Guide | NEC 2023

Depth: A minimum of 3 feet (900 mm) in front of the electrical panel for installations up to 600V. Width: The width of the equipment or panel door plus 30 inches (760 mm), whichever is ...

NEC 110.26 Spaces About Electrical Equipment

For large equipment that contains overcurrent devices, switching devices, or control devices, there shall be one entrance to and egress from the required working space not less than 610 mm (24 in.) wide ...

110.26 (C) (2) Large Equipment.

For large equipment that contains overcurrent devices, switching devices, or control devices, there shall be one entrance to and egress from the required working space not less than 610 mm (24 in.) wide ...

## Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.mastercarpetsandflooring.co.za>

Email: [info@mastercarpetsandflooring.co.za](mailto:info@mastercarpetsandflooring.co.za)

Phone: +27 82 547 3961

Address: 21 Maxwell Drive, Woodmead, Sandton, 2191, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

