

What are the specifications and models of steel strand splice boxes



Overview

Available in sizes accommodating various strand diameters, common nominal sizes include 1/4 inch, 5/16 inch, and 3/8 inch, with actual diameter ranges such as 0.259 inches for 1/4 inch splices. Standard lengths are approximately 35 inches. Preformed Line Products 1/4" Strand Splice - Galvanized Steel, Extra High Strength C-Coat (PLP GLS-2104) - The PLP GLS-2104 Strand Splice offers a simple, cost-effective solution for repairing strand or messenger lines. It consists of preformed rods made from high-strength materials like galvanized steel, aluminum, or stainless steel. This splice provides. Rated to hold a minimum of 90% of RBS of approved strands. They conform to UL 514C, CSA C22. Cord grips can with-stand tem eratures of up to 212° F (100° C).

Article Content

Splice Boxes | McMaster-Carr

Build out interfaces with buttons, gauges, and other components to monitor and control machinery. Choose from our selection of splice boxes, including over 2,400 products in a wide range of styles ...

Strand Splice Manufacturer & Supplier

Strand Splices come in various sizes to match different cable diameters and are typically rated for 100% of the strand's published breaking strength. The primary function of a Strand Splice is to restore the ...

Strand Splice

The Strand Splice is used to connect or repair guy wire or messenger strand. The strand splice has a rated holding strength which is equivalent to the rating of the wire or strand to which it is applied.

1/4" All Grade (not EHS) Strandlink, Range .240" to .253"

***Due to continuous volatility of raw material costs seen industry wide, prices and availability are subject to change without notice. Confirmed updated pricing will be returned with shipping quotes ...

1/4" Galvanized Steel Strand Splice - PLP GLS-2104

Repair guy wires and messengers with confidence using the PLP GLS-2104 1/4" Strand Splice. Engineered for full-strength performance and long-term durability. Shop now at Georgia Underground ...

Splice Connectors

"Universal" series connectors are recommended for use on Alumoweld and Extra High Strength galvanized steel strand. "All Grades" series connectors are recommended for use on common grade, ...

Orenco® Internal Splice Boxes Technical Data Sheet

Orenco splice boxes come standard with one to six watertight cord grips. Included are waterproof wire nuts, a sealing gasket, and four stainless steel lid screws. Splice boxes also come standard with ...

Strand Splice, Formed Wire Line Splice Manufacturer

Splices are made from high tensile strength and durable materials such as galvanized steel, stainless steel, aluminium, or copper. In any application, the type of splice selected should be made of the ...

1/4" Galvanized Steel Strand Splice - PLP GLS-2104

Repair guy wires and messengers with confidence using the PLP GLS-2104 ¼" ...

Strand Splice Connectors for Overhead Lines

Available in sizes accommodating various strand diameters, common nominal sizes include 1/4 inch, 5/16 inch, and 3/8 inch, with actual diameter ranges such as 0.231 to 0.259 inches for 1/4 inch ...

Technical Data Sheet Internal Splice Boxes

Internal Splice Boxes Applications as effluent pumps and float switches. They conform to UL 514C, CSA C22.2 N . 85 1968, and meet UL Type 4X rating. Cord grips can withstand temperatures of up to 212° ...

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.mastercarpetsandflooring.co.za>

Email: info@mastercarpetsandflooring.co.za

Phone: +27 82 547 3961

Address: 21 Maxwell Drive, Woodmead, Sandton, 2191, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

